

Render stop profile EJOT® Pro PAP

PAP03/01: 8810012040 | PAP06/01: 8810022040 | PAP08/01: 8810032040

PAP10/01: 8810042040 | PAP15/01: 8810040004 | PAP20/01: 8810040005

Application

Profile for creating an exact transition between different (types of) render layers as well as to finish these, e.g. with balcony undersides.

Properties

Exact and clean plaster finish

Storage and transport

lying on the entire surface; dry and frost-free; not above 50 °C; no direct sunlight

Dimensions and packaging

Bar length [m]	2
Pieces / cardboard box	25
Running meter / cardboard box	50
Cardboard box / pallet	48
Running meter / pallet	2,400
Pallet height [m]	1.3

Basic profile

Raw material	Rigid PVC – free from lead and cadmium – REACH compliant
Tolerances	Profile general tolerances 2A according to DIN 16941
Colour fastness	According to DIN EN 20105-A03 – compliance level 2

Mesh

Glass fiber fabric	R131 or comparable (certified on the basis of EAD 040016-01-0404 / EAD 040083-00-0404)
Fabric grammage [g/m ²]	160
Mesh size [mm]	4 x 4 mm
Fabric colour/print	White neutral
Fabric width [cm]	12.5 ± 5 %
Fabric fastening	welded

